

Features of MiniTest	1100	2100	3100	4100
MiniTest Memory capacity				
- Number of application memories		1	10	99
- Number of batches for each application memory		1	10	98
- Number of batches with individual value memories		1	max. 100	max. 500
- Total memory capacity for individual readings	1	10,000	10,000	10,000
MiniTest Statistics				
- From single values: \bar{x} , σ , kvar, n, max, min		●	●	●
- From single values: \bar{x} , σ , kvar, n, max, min, C_P , C_{PK}			●	●
- Block statistics: $\bar{\bar{x}}$, σ , kvar, n, max, min		●	●	●
- Block statistics: $\bar{\bar{x}}$, σ , kvar, n, max, min, C_P , C_{PK}			●	●
- From all subgroups (BATCH) in the same application (APPL)			●	●
- Print values and statistics separately to APPL-BATCH groups			●	●
- Display and print-out of date and time at the time of print-out and measurement (year, month, day, hour, minute)		●	●	●
MiniTest calibration methods				
- Calibration through a coating (CTC)		●	●	●
- Measurement on rough surfaces. The influence of roughness can nearly be eliminated	●	●	●	●
- OFFSET function adds or subtracts a constant value			●	●
- External function (trigger) to transfer readings to the memory	●	●	●	●
- Key lock to protect calibration	●	●	●	●
- Readings are saved during battery replacement	●	●	●	●
- Limit setting			●	●
- Measurements in microns or mils	●	●	●	●
- Continuous measuring mode with high speed readings to identify minimum and maximum values	●	●	●	●
- Selectable stabilising procedure in continuous mode for quick display (7 readings/s)	●	●	●	●
- Data transfer with floating or fixed decimal point	●	●	●	●
- Reading of measuring values without probe being connected		●	●	●
- Later print-out of single values of one batch		●	●	●
- Display of minimum value in continuous mode	●	●	●	●